

# Heavy Duty Cutter

## PULL TYPE

BUY KODIAK

8'

10'



Side To Side  
Adjustable Wheel Spacing.



8 ft.	SPECIFICATIONS	10 ft.
93"	Cutting Width	116"
98"	Transport Width	122"
Center Pull Self Leveling	Type Hitch	Center Pull Self Leveling
2" to 12"	Cutting Height	2" to 12"
3" dia. material	Cutting Capacity	3" dia. material
10 GA Steel	Deck Thickness	3/16" or 7 GA Steel
HD 8" Channel	Side Bands	HD 8" Channel
Fold up - removable	Tongue Jack	Fold up - removable
<b>36 HP</b>	Recomm. Min. HP	<b>42 HP</b>
3x8 with hose	Hydraulic Cylinder	3x8 with hose
Constant Velocity w/slip	PTO	Constant Velocity w/slip
Shock Coupler Protected	Center Drive Shaft	Shock Coupler Protected
5/8" thick, round	Stump Jumper	5/8" thick, round
100 HP center box	Gear Box	100 HP center box
2- 90 HP outboard	Gear Boxes	2- 90 HP outboard
21" Laminated	Tail Wheels	21" Laminated
Ball Bearing	Spindle Hubs	Ball Bearing
Optional	Front/Rear Chain Guard	Optional
1410 lbs.	Weight	1790 lbs.
Replaceable	Skid Shoes	Replaceable

Specifications are subject to change without notice.

## 5200 Series: Pull-Type Cutters

KODIAK's Heavy Duty Pull Cutters are made for a wide range of cutting heights up to 12". Now you can have the most flexibility for tough jobs backed with the power of a 100 HP/90 HP outboard gear box. Built with solid construction to last for years of dependable service.

### WARNING

KODIAK recommends that all customers purchase front and rear safety chain shielding in all applications to prevent injury or death.