

Professional Line

ProTeam



FERRI[®]

Front and rear mowers
for professional green
maintenance and agriculture

MKD

MKD 2300-2500-2800





Professional Line



Front and rear mowers for professional green maintenance and agriculture

The MKD mowers are multitasking machines targeted to the green maintenance professionals and they are specifically designed for tractors with rear and front P.T.O. Therefore, the design has paid particular attention to the details that distinguish a professional machine from a traditional shredder. The rotor benefits from the helical arrangement of the cutting tools to evenly distribute the workload and allow the best balancing obtaining a significant vibration reduction. The counterweights are distributed on the balancing discs and not welded to the rotor. The frame is characterized by an encased structure with two separate beams, one in the front and the other in the upper section to ensure

the best ratio between weight and rigidity. Other details such as the tubular skids, the roller with bolted flanges and the belt transmission with its belt tightener place the MKD series at the top of the professional shredders.



Max. modularity. Revolving upper 3 point linkage for front and rear mounting.




SAFETY



Front protection with steel flaps



Rubbercloth wear-resistant rear protection



Inner lining (for better rotor housing protection)

Protections accident prevention in accordance with EC regulations

Tractor		75	85	95	105	115	130
HP/PS							
MKD 2300		[Green bar]					
MKD 2500			[Green bar]				
MKD 2800				[Green bar]			

FERRI®



MKD 2300-2500-2800



RELIABILITY



Double shaft gearbox

Hydraulic sideshift (the tractor must be equipped with double acting oil outlet)

MKD 2300:
Pto 1000/540 RpM

PERFORMANCE



6 row spiral rotor with balancing end shields. Rotor bearings internally fitted

Steel plate for cutting adjustment



Rear adjustable roller Ø 6 1/2" (4 positions). Screwed bearing housing



Adjustable axial floating belt tensioner (ensures durability limiting the power dissipation in heat)

TECHNICAL

Pto shaft with free wheel (depending on the use Front, Rear or Revers of the flail mower). hydraulic side shift

Hydraulic hoses with quickcouplings

Tubular and wear resistant side skids (they facilitate the side sliding of the mower)



Front and rear mowers for professional green maintenance and agriculture



Working positions (ft)	
MKD 2300	3'10" 3'10" 2'4" 5'4"
MKD 2500	4'2" 4'2" 2'8" 5'8"
MKD 2800	4'6" 4'6" 3' 6'

Technical data	MKD		
	2300	2500	2800
Model	2300	2500	2800
Cutting width	ft 7'6"	8'2"	8'11"
Max Sidesliding	ft 8'2"	8'9"	9'7"
Belts	N° 4	4	5
Weight	lbs 1929	2216	2304
Tractor	HP 75/130	85/130	95/130
Hydraulic side shift	ft 1'11"	2'3"	2'3"
Pto	Rpm 1000/540	1000	1000
Blade tip speed	ft/sec 177	167	167

Flails	
Interchangeable on the same rotor	
A	Multiuse flails for: grass, bushes, shrubs, sticks, wood Ø max 1 3/4"
B	Forged hammer-blades for: woods, twigs, grass Ø max 2"

MKD		
2300	2500	2800
A - B (72 - 24)	A - B (78 - 26)	A - B (84 - 28)

All data subject to change campbellacw.com 73115 MKD - USA - EN Rev.2 - 1060



FERRI srl
 Via Govoni, 30
 44034 Tamara (FE) Italy
 Tel. +39 0532 866866
 Fax +39 0532 866851
 info@ferrisrl.it - www.ferrisrl.it



North America Sales and Marketing Manager / FERRI
 Ronald E. Roglis - Glenarm, Illinois 62536
 Cell (314) 422-9460 - Fax (217) 483-4123
 ron.roglis@gmail.com

Parts Stock / FERRI:
 J.S. Woodhouse Co., Inc. - 1314 Union Street
 P.O. Box 1169 - West Springfield, Ma. 01090 U.S.A.
 tel. 413-736-5462 - fax 413-732-3786
 info@jswoodhouse.com

www.ferri-america.com