

with a PROFESSIONAL Quality Goossen Chipper

Available in towable gas engine or PTO drive models.



A Division of Harper Industries, Inc.

151 East Hwy. 160 • Harper, KS 67058 1-800-835-1042 • www.goossen.com email: goosseninfo@deweze.com


- Double-wall, 10-gauge steel drum housing, capable of handling the pounding of chipping and shredding heavy material.
- Hinged housing provides easy access to drum for changing knives.
- The Chipping Rotor is 18" diameter, ³/₄" machined, steel plate–weighs 115 lbs.
- Up to 5" diameter limbs and branches.
- Hopper cover on shredder restricts material kick-back for maximum safety.
- Folding safety door on hopper keeps operator away from chipper knives, and prevents material kick-back when closed.



Designed for proper feeding height-great when handling hardwood limbs up to 5" diameter.



blower attachment) requires 18 to 30 HP tractor with 540 RPM PTO.





18 HP Honda engine powers trailer mounted model with optional blower attachment.

SPECIFICATIONS	
Shredder Hopper Size	34" x 21"
Chipper Plate	18" dia. 3/4" machined and balanced steel plate
Chipper Capacity	5" maximum diameter material
Shredder	36 free-swinging serrated knives
Chipper Knives	4 knives honed from tool steel
Chipper Chute	33"L x 13"W x 12"H
Shredder Capacity	1" to 1 ¹ / ₄ " maximum diameter material recommended
Chip Sizing Grate	1 ¹ / ₂ " grate is standard, (¹ / ₂ ", ³ / ₄ ", and leaf bar optional)

Approximate Shippin	g Weight
Gas	940 lbs
PTO	560 lbs
Power Requirements	
Gas	18 hp Honda engine
PTO	540 PTO at 18 hp to 30 hp*
Optional Equipment	
Blower Attach	ment with Directional Spout
* warranty may be void if used	on tractors over 35 hp

Distributed by:



A Division of Harper Industries, Inc.

151 E. Hwy. 160 • Harper, KS 67058 1-800-835-1042 • www.goossen.com email: goosseninfo@deweze.com