

## FSP 100/150

Spreaders for green areas and garden use.
The FSP series spreaders are designed to be used on small tract.,
garden vehicles and trucks, without P.T.O. shaft.

These spreaders can be used for spreading fertilizers, sand or salt depending on the needs of users.

The movement of the wheels through the gearbox, fitted on the main axle, makes the spreading disc turn.

The forward speed determines the spreading width. By acting on the lever it is possible to increase or decrease the quantity of product

On request, this spreader can be supplied with a deflector for spreading salt or sand that allows spreading the product only below



SPECIFICATIONS													
	Model	Hopper Capacity		Maximum loading capacity		Width of spreading pattern depending on spreading material		Overall height		Hopper width		Required power	
		litre	USA Gallons	KG.	LIBS	Metre	Yards	Metre	Inch	Metre	Inch	HP	KW
	FSP 100	100	26,5	46	100	2 ÷ 6	2,2 ÷ 6,5	1,00	40	0,8	32	4	3
	FSP 150	144	38	61	135	2 ÷ 6	2,2 ÷ 6,5	1,35	42	0,9	36	4	3

SITREX S.p.A. reserves the right to make changes or add improvements at any time without notice. The information contained herein is general in nature and is not intended for specific application purposes.



Zona Industriale - Viale Grecia, 8 06018 TRESTINA (Perugia) - ITALY Phone ++39 075 8540021 - ++39 075 8540523 E-mail: sitrex@sitrex.it - http://www.sitrex.com