



SSL ANGLE SWEEPER-HYDRAULIC DRIVE (QCSS ANGLE)

For Skid Steer Loaders



The **Sweepster QCSS Angle Sweeper**, by Paladin, has a faceted hood design that provides maximum strength at the ends of the hood where most stress and damage occur.

- Available in 60", 72", 84" and 96" widths
- 32" diameter brush
- Quick change core



Primary Prime Mover	Additional Prime Movers	Sweeper Group	Mount Type	PTO Type	Brush Diameter	Mechanical Angle	Hydraulic Angle	Brush Width	Quick Change Core	Feature Details	Application
Skid Steers	None	Angle Sweepers	Front Mount	N/A	32"	Standard	Option	5, 6, 7, 8 ft.	Yes	For SSL with 10-36 GPM @2000-3500 PSI. Includes universal quick attach.	Heavy duty cleanup

SSL ANGLE SWEEPER-HYDRAULIC DRIVE (QCSS ANGLE)

- No hydraulic line breakage when changing core
- Mounts to existing mountings/ interchangeable with S/D32 Series tractor/ truck and loader mountings
- Fold away stands
- Modular design - can easily change single into dual or dual into single
- Replaceable hex drive system
- Universal skid-steer mounting standard, other quick attach optional mounts available
- Manual angle change 30° left to 30° right is standard
- Optional hydraulic angle with electric valve
- Optional dirt deflector
- Optional 180° hood
- Optional dust suppression system
- Optional single to dual and dual to single conversion
- Optional PTO driven hydraulic systems
- Choose from poly, wire, or poly/wire brushes
- Optional tube brush configuration

Specifications - Single Motor							
Model Number	22059	22060	22071	22072	22083	22084	22096
A. Overall Height	33.5"	33.5"	33.5"	33.5"	33.5"	33.5"	33.5"
B. Overall Width @ 0°	74.8"	74.8"	86.8"	86.8"	98.8"	98.8"	110.8"
C. Overall Length @ 0°	68.5"	68.5"	68.5"	68.5"	68.5"	68.5"	68.5"
D. Sweeping Width @ 0°	60.0"	60.0"	72.0"	72.0"	84.0"	84.0"	96.0"
E. Overall Length @ 30°	77.0"	77.0"	80.0"	80.0"	83.0"	83.0"	86.0"
F. Overall Width @ 30°	75.2"	75.2"	85.6"	85.6"	96.0"	96.0"	106.4"
G. Sweeping Width @ 30°	52.0"	52.0"	62.4"	62.4"	72.8"	72.8"	83.2"
H. Center of Gravity	33.5"	33.5"	34.3"	34.3"	35.2"	35.2"	35.9"
Weight (lbs)	793	831	852	890	915	953	1020
Flow Range (GPM)	10-18	12-25	10-18	12-25	10-18	12-25	12-25
Hydraulic Motor Displacement (C.I.)	18.3	28.3	18.3	28.3	18.3	28.3	28.3
# of Motors	1	1	1	1	1	1	1
Maximum Pressure (PSI)	3500	3000	3500	3000	3500	3000	3500
Maximum Articulation	30°	30°	30°	30°	30°	30°	30°
Brush Diameter	32"	32"	32"	32"	32"	32"	32"

Specifications - Dual Motor				
Model Number	22061	22073	22085	22097
A. Overall Height	33.5"	33.5"	33.5"	33.5"
B. Overall Width @ 0°	74.8"	86.8"	98.8"	110.8"
C. Overall Length @ 0°	68.5"	68.5"	68.5"	68.5"
D. Sweeping Width @ 0°	60.0"	72.0"	84.0"	96.0"
E. Overall Length @ 30°	77.0"	80.0"	83.0"	86.0"
F. Overall Width @ 30°	75.2"	85.6"	96.0"	106.4"
G. Sweeping Width @ 30°	52.0"	62.4"	72.8"	83.2"
H. Center of Gravity	34.0"	34.8"	35.6"	36.2"
Weight (lbs)	831	890	953	1020
Flow Range (GPM)	20-36	20-36	20-36	20-36
Hydraulic Motor Displacement (C.I.)	18.3	18.3	18.3	18.3
# of Motors	2	2	2	2
Maximum Pressure (PSI)	3500	3500	3500	3500
Maximum Articulation	30°	30°	30°	30°
Brush Diameter	32"	32"	32"	32"

