





Wheel track eradicators



Counter flanges



PTO shaft with friction disc slip clutch



Side gear drive




Gearbox detail



Front wheels for working depth adjustment

| | 1000 rpm | rpm |
|--|----------|-----|
| | 22-19 | 161 |
| | 22-19 | 178 |
| | 22-19 | 196 |
| | 18-22 | 216 |
| | 18-22 | 238 |
| | 18-22 | 263 |

| MODEL | HP | Working width Inches | Total width Inches | Inches | Blades | Lbs |
|----------------|---------|-------------------------|-----------------------|--------|--------|------|
| G - 300 | 180-250 | 123 | 132 | 59 | 72 | 4195 |
| G - 350 | 200-250 | 143 | 152 | 69 | 84 | 4906 |
| G - 400 | 220-250 | 163 | 172 | 79 | 96 | 5632 |



Working depth 12 inches



MASCHIO USA
432 2ND Street
Rock Island, IL 61201 USA
Ph. +1 309 794-2310
Fax +1 309 788-1610



MASCHIO-GASPARDO CANADA Inc
2275, rue Power
Drummondville, Qc
J2C 6Z5 CANADA
Ph. 819.477.1107
Fax 819.477.1108

DEALER:

MASCHIO

MOD. **G**



ROTARY TILLERS 90 ÷ 250 HP

Rotary tillers for tractors from 66 to 184 kW (90-250 HP) with skids or with roller, side gear drive and gearbox with 540 and 1000 rpm P.T.O.

Standard Equipments

- 3 speed gearbox r.p.m. P.T.O. with hand lever
- Cam clutch P.T.O. shaft
- Side gears drive
- Universal three point hitch, cat. II and III
- Swinging lower hitches
- Rear P.T.O.
- 6 blades per flange (side blades are mounted inwards)
- Bonnet spring adjuster
- Mechanical rear roller adjusters
- EC safety guards

Optional Equipments

- Hydraulic rear roller side adjusters
- Gearbox oil cooler
- Hydraulic seed drill hitch
- Front pair of wheels for working depth adjustment
- Wheel track eradicators
- RH, LH side disk share