



10784 Industrial Parkway
Marysville, OH 43040

Tel: 614-873-4620
Fax: 614-873-8584
Toll Free: 888-222-8455

HD/8 Feature and Benefit

The HD/8 delivers 30,000 lbs of impact force at full stroke.

- The HD/8 will drive a 4"-5" post in 10 seconds or less in ideal conditions
- In ideal conditions the HD/8 can drive post up to 7.5".
- In most conditions the HD/8 will drive post in 10-20 seconds.

The HD/8 has only 8 moving parts.

- By minimizing moving parts fail points are reduced resulting in considerable savings in operating cost over other machines.
- Serviceable components are stocked and readily available at dealers, distributors, and warehouses' to get you back to work quickly reducing lost time.
- The simple straight forward design allows for repairs and maintenance to be done in the field by the user. This reduces repair and service cost over other machines.

The HD/8 tilts up to 15 degrees front to back and left to right.

- Allows the user to adjust the driver to terrain to maintain a straight fence line.
- Allows the user to adjust the driver between strikes, allowing the user to drive the post straight as it hits rocks and tough soil.
- Allows the user to apply pressure to a post that needs to be straightened as it is driven.

The HD/8 can mount on a Category I three point hitch.

- Allows the user to utilize smaller tractors to maneuver into less accessible areas.
- By utilizing a smaller tractor the user will incur less fuel cost than on a larger machine.
- The Cat I hitch provides opportunity to mate the driver with most tractors.

The HD/8 requires only 3-4 GPM to operate.

- Allows the use of the HD/8 on virtually any size tractor with auxiliary hydraulics.
- The HD/8 will have a diminutive effect on the host tractor hydraulics, causing no wear and tear while in use.
- The low hydraulic requirements give the user an opportunity to mount the driver on a very broad age range of tractors.

Overview:

The HD/8 is an occasional use, low maintenance, driver designed to give property owners the ability to drive 4"-5" post in most conditions on most terrain. It will save considerable time and money over operating other machines and methods of placing post.