





Paladin Attachments is your single source for high quality attachments for skid steers, compact tool carriers, and excavators used for vegetation/land management, landscaping, soil preparation, material handling, and construction.

FFC by Paladin tillers are perfect for landscaping and site preparation. They turn up hard packed ground leaving the perfect seedbed for gardens or lawns.

- Breaks up sod and clumps of soil
- Mixes compost and other materials
- Prepares soil for seeding or reseeding; great for small soil stabilization and landscape jobs
- Available as fixed offset with dual direct drive or adjustable offset with chain drive







Tillers Fixed Offset, Dual Direct Drive

- Dual direct drive motors propel both ends of the tiller drive shaft for balanced torque and minimal wear and tear
- Offset tiller mounting permits work up close to walls, building and pipes, covers 76" wheel tracks
- Available in 38", 52", & 68" working widths
- Hardened, replaceable tines cut to 6" deep
- 1 year warranty on structure, 6 month warranty on hydraulics



Cresifications	Fixed Offset, Dual Direct Drive			
Specifications	38"	52"	68"	
Order Codes	LAF3438	LAF3452	LAF3468	
Weight (lbs)	435	600	695	
Working Width	38"	52"	68"	
Overall Width	44"	68"	78"	
Number of Tines	20	28	36	
GPM Range	6 to 12	12 to 40	15 to 40	
PSI Range	1,500-3,000	2,000-3,500	2,300-3,500	
Torque @2,500 PSI	470 ft-lb	939 ft-lb	939 ft-lb	
Lift Capacity	<9,000 lbs	<9,000 lbs	<9,000 lbs	
Operating Weight	<11,000 lbs	<11,000 lbs	<11,000 lbs	

Bi-directional shaft rotation permits under cutting and topcutting in both directions of travel



Specifications and design are subject to change without notice and without liability, therefore, whenever applicable specifications are in accordance with SAE standards.















Tillers Adjustable Offset, Chain Drive



- High torque efficient chain drive system
- Exclusive two position offset mount on 66" & 78" tiller covers wheel tracks and allows tight cut next to obstacles
- Available in 52", 66", & 78" working widths
- 2 year limited warranty

Specifications	Adjustable Offset, Chain Drive				
Specifications	52"	66"	78"		
Order Codes	HT52	HT66	HT78		
Weight (lbs)	750	1,000	1,300		
Working Width	52"	66"	78"		
Overall Width	62"	76"	88"		
Number of Tines	24	32	40		
Number of Scarifier Teeth (opt)	4	5	6		
Recommended Hydraulics					
Motor Kit #102065	14-17 GPM	14-17 GPM	NA		
Motor Kit #102066	18-28 GPM	18-28 GPM	NA		
Motor Kit #102065	NA	29-44 GPM	29-44 GPM		

Standard dual rotation with bi-directional tines



Scarifier assembly increases productivity by combining the tractive effort and force of the loader with the hydraulic horse power of the tiller



Specifications and design are subject to change without notice and without liability, therefore, whenever applicable specifications are in accordance with SAE standards.















When work needs to get done you need to be able to depend on your equipment. Our material handling attachments are designed for maximum reliability, durability, and productivity.



BRADCO CP **CUSTONWORKS** McMillen

FFC

HARLEY J:B **SWEEPSTER**





