A 5KIBO COMPANY ®



Wagon Gear

Heavy payloads are no problem for Pequea wagon gear. They are manufactured with large, reinforced spindles & oversized axles to handle big loads smoothly and efficiently. Tapered roller bearings keep the load stable on field or highway transport with features including automotive-type steering, equiflex suspension & sintered bronze bushings at all wear points. Pequea wagon gear give you years of service under demanding requirements and offer seven adjustments to choose the capacity you need.



Wagon Gear					
Specifications	606	806	1086	1286	1288
Capacity	12,000	16,000	20,000	24,000	
Spindle	1 3/4"		2"	2 3/4"	
Hubs	6 Bol	888 6 Bolt 783		8 Bolt	
Bearings	Tapered Roller				
Pole Reach	8' x 2 5/8"	8' x 2 7/8"			8' x 3 5/8"
Optional	10', 12', 14'				
Post Spacing	38" or 42"				
Rear Hitch	Yes				
Tongue	Adjustable 92" - 128"				
Optional	Adjustable 72"- 108"	Adjustable 116" - 152"			
Spring Assist	N/A	Standard			
Track Width	73"		81"		85"
Wheels	15 x 6	15 x 8	15 x 10		
Axles (Bolsters)	3 x 5 1/2 x 9G Formed Steel	3 1/4 x 7 1/4 x 3/16 Formed Steel	4 x 8 x 3/16 Tubing		4 x 10 x 1/4 Tubing
Weight (Less Tires)	515 lbs.	728 lbs.	883 lbs.	1090 lbs.	1240 lbs.

Pequea reserves the right to change specifications, design and price of products described in this literature without notice. © 2011 Pequea.