



MOD. B




Wheel track eradicators



Double flanges (opt)



PTO shaft with slip clutch (std)



Gear side drive (std)




Multi speed gearbox, detail (std)



Twin rear depth control wheels

540 rpm	rpm	MODEL	HP	Working width Inches	Total width Inches	Inches	Blades	Lbs
22-16	140	B 155 (62)	45 - 100	62	68	32	36	1195
20-18	174	B 180 (72)	50 - 100	72	78	36,5	42	1294
18-20	213	B 205 (82)	60 - 100	82	88	41	48	1397
16-22	266	B 230 (92)	70 - 100	92	98	46,5	54	1496



Working depth 10 inches



MASCHIO USA
432 2ND Street
Rock Island
IL 61201 USA
Ph. +1 309 794-2310
Fax +1 309 788-1610



MASCHIO-GASPARDO CANADA Inc
2275, rue Power
Drummondville, Qc
J2C 6Z5 CANADA
Ph. 819.477.1107
Fax 819.477.1108

DEALER:



Technical data and models shown into this catalogue are not binding. We reserve the right to revise the contents of this catalogue, to amend or improve the specifications without notice.



MASCHIO

MOD. **B**



ROTARY TILLER 40 ÷ 100 HP

Rotary tiller with a considerable variety of uses thanks to its wide choice of set-up and accessories. Its structure satisfies small and medium farms needs and achieve excellent results on even very difficult soils with considerable economy in the use of tractor power.

Standard Equipments

- Multi speed gearbox 540 r.p.m. P.T.O.
- P.T.O. shaft with slip clutch
- Gear side drive
- Universal three point hitch, cat. I and II
- Adjustable offset lower hitches
- 6 blades per flange (side blades are mounted inwards)

Optional Equipments

- Double flanges
- Twin rear or front depth control wheels (pin adjustable)