



MOD. **C**



COBRA rotor




Twin depth control wheels (opt)



PTO shaft with slip clutch (std)



PTO shaft with cam clutch (opt)




Gear side drive (std)



Multi speed gearbox, detail (std)

rpm		rpm		MODEL	HP	Working width Inches	Total width Inches	Inches	Blades	Lbs
rpm	540 rpm	1000 rpm	rpm							
	21-19	175	324	C 205 (82)	60 - 130	82	88	42	48	1487
	23-17	143	265	C 230 (92)	70 - 130	92	98	46,5	54	1588
	24-16*	129	239	C 250 (102)	80 - 130	102	108	51	60	1694
	22-18*	158	293	C 280 (112)	90 - 130	112	118	56,5	66	1804
	19-21	214	-	C 300 (122)	100 - 130	122	128	61	72	1914
	17-23	262	-							
	16-24*	290	-							
	18-22*	236	-							

* Optional gear sets



Working depth 10 inches



MASCHIO USA
 432 2ND Street
 Rock Island
 IL 61201 USA
 Ph. +1 309 794-2310
 Fax +1 309 788-1610



MASCHIO-GASPARDO CANADA Inc
 2275, rue Power
 Drummondville, Qc
 J2C 6Z5 CANADA
 Ph. 819.477.1107
 Fax 819.477.1108



DEALER:

Empty box for dealer information.

Technical data and models shown into this catalogue are not binding. We reserve the right to revise the contents of this catalogue, to amend or improve the specifications without notice.





MASCHIO

MOD. **C**



ROTARY TILLER 60 -130 HP

Rotary tiller with a wide variety of uses, suitable for medium/large farms and medium power tractors. The preparation of the ground after plowing, the working in of stubble and crop residues, the mechanical control of weeds, the breaking up of established grassland, direct preparation without plowing - these are only some of its many possible uses. This model is available in a version with Cobra type blade rotor.

Standard Equipments

- Multi speed gearbox 540/1000 r.p.m. P.T.O.
- P.T.O. shaft with slip clutch
- Gear side drive
- Universal three point hitch, cat. II
- Floating lower hitches
- 6 blades per flange (side blades are mounted inwards)

Optional Equipments

- P.T.O. shaft with cam clutch
- Rear P.T.O.
- Counter flanges
- Twin depth control wheels
- RH, LH side disc