

MOD. **L**



Universal three point hitch, cat. I



Rear door: chain



PTO shaft with shear pin (optional)



Chain side drive




Skids for working depth adjustment



Detail of blade

rpm	rpm	MODEL	HP	Working width Inches	Total width Inches	Offset (Inches)	Blades	Lbs
540	254							
		L 85 (34)	10 - 25	34	38	16,5 14,5	16	260
		L 105 (42)	15 - 25	42	46	20,5 16,7	20	293
		L 115 (45)	18 - 25	45	54	22,5 14,5	20	308
		L 125 (50)	20 - 25	50	62	24,5 16,5	24	323



Working depth 6,00 inches



MASCHIO USA
432 2ND Street
Rock Island,
IL 61201 USA
Ph. +1 309 794-2310
Fax +1 309 788-1610



MASCHIO-GASPARDO CANADA Inc
2275, rue Power
Drummondville, Qc
J2C 6Z5 CANADA
Ph. 819.477.1107
Fax 819.477.1108

**COMPANY
WITH QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001/2000 =**

DEALER:

Technical data and models shown into this catalogue are not binding. We reserve the right to revise the contents of this catalogue, to amend or improve the specifications without notice.



MASCHIO

MOD. **L**



ROTARY TILLER 10 ÷ 25 HP

Adjustable offset rotary tiller of small dimensions, recommended for hobby farmers and small farms, suitable for vineyards, orchards, vegetable crops and gardening. Particularly designed to have a sturdy build and a low power requirement to match light tractors.

Standard Equipments

- Single speed gearbox with 540 r.p.m. P.T.O.
- Standard P.T.O. shaft
- Chain side drive in oil bath
- Universal three point hitch, cat. I
- Three point hitch manual offset
- 4 blades per flange (side blades are mounted outwards)
- Mechanical adjustable offset

Optional Equipments

- P.T.O. shaft with shear pin
- P.T.O. shaft with slip clutch